

1/7/3 (Item 3 from file: 351)  
DIALOG(R)File 351:Derwent WPI  
(c) 2004 Thomson Derwent. All rts. reserv.

007693682

WPI Acc No: 1988-327614/ 198846

Packaging material for foodstuffs, etc. - comprises plastic film plasma treated in nitrogen (contg.) atmos. and metal vapour deposition layer formed using adhesive

Patent Assignee: TOPPAN PRINTING CO LTD (TOPP )

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
-----------	------	------	-------------	------	------	------

JP 63242534	A	19881007	JP 8777333	A	19870330	198846 B
-------------	---	----------	------------	---	----------	----------

Priority Applications (No Type Date): JP 8777333 A 19870330

Patent Details:

Patent No	Kind	Lan Pg	Main IPC	Filing Notes
-----------	------	--------	----------	--------------

JP 63242534	A	3		
-------------	---	---	--	--

Abstract (Basic): JP 63242534 A

The packaging material is composed of a plastic film having its surface low temp. plasma treated in an atmos. of nitrogen gas or a mixed gas contg. nitrogen gas, and a metal vapour deposition layer formed on the plasma-treated surface of the film through an adhesive. The plastic film is pref. formed of a polyamide resin or a polyethylene terephthalate resin.

---

USE/ADVANTAGE - For packaging of foodstuffs, etc. This material is laminated to a heat adhesive film of PE, PP, etc. to form a retort-sterilisation packaging material. The low temp. plasma treatment provides a high delamination resistance even after retort sterilisation.

In an example, A 15 microns thick nylon film was low temp. plasma treated. The film was laminated to a 70 microns thick non-oriented PP film through an adhesive. (The delamination strength before retorting 400 g/15 mm, that after retorting 400 g/15 mm).

0/0

**BEST AVAILABLE COPY**